



Item		BO 12 40 X	BO 12 60 X	BO 12 80 X
Suction plate	item	PX 12 40	PX 12 60	PX 12 80
Gripping force	Kg	25.7	42.2	56.3
Fitted for vacuum generators	item	N°1 PVP 25 MX PBO	N°2 PVP 25 MX PBO	N°2 PVP 25 MX PBO
Maximum supply pressure	bar	6	6	6
Maximum level of vacuum	-KPa	90	90	90
Air consumption at 6 bar	NI/s	3.2	6.4	6.4
Intake air flow rate	m³/h	31	62	62
Temperature of use	°C	-20 / +80	-20 / +80	-20 / +80
Weight	Kg	4.5	8.1	10.8
A		400	600	800
B		120	120	120
C		21	21	21
D		90	90	90
E		5.2	5.2	5.2
F		4.8	4.8	4.8
G		10	10	10
H		112	112	112
P	Connection for compressed air tube	Ø ext. 8	8	8

NOTE: The code BO 12 .. X identifies the body of the OCTOPUS bar with relative suction plate PX, the grooved support plate and the vacuum generators indicated in the table.

Add the letters CD to the item for an Octopus bar supplied without vacuum generators and with closing plates with distributor item 00 BO 07 assembled (Example: BO 12 60 X CD).

NOTE: All vacuum values indicated in the table are valid at the normal atmospheric pressure of 1013 mbar and obtained with a constant supply pressure.

Vacuum generator supply must be carried out with non-lubricated compressed air, 5 micron filtration, in accordance with standard ISO 8573-1 class 4.

Transformation ratio: N (newton) = Kg x 9.81 (force of gravity)

inch =  $\frac{\text{mm}}{25.4}$  ; pounds =  $\frac{\text{g}}{453.6} = \frac{\text{Kg}}{0.4536}$